



UNITEST TELARIS® Loop

Key Functions

- Measurement of loop resistance and prospective short circuit current measurement without tripping the RCD
- Line resistance and prospective short circuit current measurement
- Enables the user to measure each conductor resistance independently: PE resistance, phase resistance and neutral resistance
- Voltage and frequency measurement

General Information

- Integrated memory for approx. 250 measurement values
- Standard, built-in IR/RS-232 interface for transferring measurement data to the PC
- UNITEST software for recording test results is available as option
- Integrated socket test with contact electrode to enable the user to quickly establish incorrectly installed sockets and/or protective conductor failures
- Pre-selection of max. admissible contact voltage
- Clear and large LCD providing the user with an optimum visual indication of both test values and limits
- Auto power off

Special Features

- Patented measurement principle of loop resistance and prospective short circuit current measurement without tripping the RCD



Technical data

Display	3½ digit; LCD; 1999 Digits
Measurement range / Resolution / Tolerance	0.05...1999Ω/0.01...1Ω/ ±(5%rdg.+5Digits)
Loop impedance	0.05...19.99Ω/0.01/ ±(5% rdg.+ 5 Digits)
Line resistance	0.05...19.99Ω/0.01/ ±(5% rdg.+ 5 Digits)
Resistance neutral connector	0.05...19.99Ω/0.01/ ±(5% rdg.+ 5 Digits)
Resistance earth connector	0.05...1999Ω/0.01...1Ω/ ±(5%rdg.+5Digits)
Resistance phase connector	0.05...19.99Ω/0.01/ ±(5% rdg.+ 5 Digits)
Prospective short circuit current	1 A...4.6 kA / 1 A,10 A
Voltage	0...300 V / 1 V / ±(3% rdg.+3 Digits)
Mains frequency	10...200 Hz/0.1 Hz/ ±(1% rdg.+ 2 Digits)
Contact voltage	25 V / 50 V (selectable)
Data memory	approx. 250 Meas. values
Interface	IR / RS-232 interface-adapter
Protection class	II (double insulated)
Safety complying with	IEC61010/EN61010/ DIN VDE 0411 IEC61557/EN61557/ DIN VDE 0413
Measurement category	CAT III / 300 V
Pollution degree	2
Protection degree	IP 50
Auto-Power-Off	
Power supply	1 x 9 V, IEC 6LR61
Dimensions	235 x 105 x 70 mm
Weight	approx. 500 g

Scope of Supply:

1 pc UNITEST TELARIS LOOP
 1 pc Test lead with Schuko plug system
 1 pc Test lead 3-pole
 3 pc Crocodile clamps
 3 pc Test Probes
 1 pc Protective Holster
 1 pc Carrying Case
 1 pc Battery 9 V, IEC 6LR61
 1 pc Instruction Manual



Accessories:

- UNITEST Software „es control 0100“ without interface adapter Cat. No. 1251
- UNITEST Software „es control professional 0100“ without interface adapter Cat. No. 1312
- UNITEST Software „Report-Studio VDE“ without interface adapter Cat.-No. 1200

Interface adapter
Cat. No. 1157

Professional Carrying Case
Cat.-No. 1229

Order Information:

Description	Cat. No.
UNITEST TELARIS Loop	8978
UNITEST Software „es control 0100“ without interface adapter	1251
UNITEST Software „es control professional 0100“ without interface adapter	1312
UNITEST Software “Report-Studio VDE” without interface adapter	1200
Interface adapter	1157
Professional Carrying Case	1229