

Voltage and Continuity Tester



Model: 90050



Voltage test : 12V, 24V, 50V, 127V, 230V, 400V, 690V/AC/DC

Continuity test : 6k Ω , 60k Ω , 300k Ω

Probe Distance : 19mm apart



Features:

- Voltage test : 12 to 690V AC/DC (7 LEDs) with indication by buzzer.
- Voltage range : 12V, 24V, 50V, 127V, 230V, 400V, 690V.
- Resistance range : 6k Ω , 60k Ω , 300k Ω .
- Test leads positioned at 19mm apart.
- Polarity test : LED \pm
- Audible continuity test
- Self-test button to ensure proper function of the device prior to testing.
- Integrated storage clips for test probe.
- Rubberized injection molding.

Technical Data:

Display	9 LEDs
Voltage Test	12 to 690V AC/DC
Voltage Range	12V, 24V, 50V, 127V, 230V, 400V, 690V
Working Frequency	0 to 400 Hz
Voltage Protection	1000V DC / 700V AC
Continuity Range	6k Ω
Resistance Range	6k Ω , 60k Ω , 300k Ω
Operating Temperature	0 to 40°C
Operating Humidity	80% RH
Probe Distance	19mm apart
Power Supply	1 x 9 V, IEC 6LR 61
Dimensions (mm)	260 x 58 x 42 mm
Weight	Approx. 210g (battery included)
Electrical Safety	IEC 61010-1 CAT III 600V, IEC 61243-3

Scope of Supply:

- 1 pc Voltage and Continuity Tester 90050
- 1 pc Battery 9V, IEC 6LR61
- 1 pc Carrying Case
- 1 pc Instruction Manual

