

CAT III
600 V

LED
10

12...
690 V

HDT Voltage Tester 3001



Features:

- AC/DC Voltage Measurement up to 690 V
- Continuity test function with optical and acoustical indication up to 200 k Ω
- Integrated single pole test for phase detection
- Automatic AC/DC voltage measurement selection
- Bright LED display
- Fully operational voltage display even when batteries are discharged or when no batteries are fitted
- Rugged, ergonomically formed housing for perfect handling
- Quick single hand test on 19 mm contact distance outlets
- Probe-tip protection for reducing the danger of injuries which may caused by probe-tips

Technical Data:

Display	10 LED (+12 V, -12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V, Single Pole, Continuity)
Voltage Range	12...690 V
Polarity Indication	automatic
Frequency Range	DC, 0...65 Hz
Test Current	< 3.5 mA
Single Pole Voltage Test	100...690 V AC
Continuity/Diode Test	optical / acoustical
Measurement Cat.	CAT III / 600 V
Protection Degree	IP 54
Pollution Degree	2
Safety	EN 61010, EN 61243-3
Power Supply Batteries	2 x 1.5 V, IEC LR03 / AAA
Dimension	approx. 205 x 67 x 27 mm
Weight	approx. 130 g

Scope of supply:

1 pc HDT Voltage Tester 3001, 2 pcs Batteries, 1.5 V IEC LR03 / AAA
1 pc Instruction Manual, 1 pc 4C gift box

Order information Description

HDT Voltage Tester

Order No.

3001

Hoover Dam Technology GmbH

In den Engematten 16 · 79286 Glottertal / Germany

Tel. +49 (0) 7684 907 - 200 · Fax. +49 (0) 7684 907 - 101

Email: info@hdt-electronic.com · Internet: www.hdt-electronic.com

linking people
and technology

Shanghai Beihan Electronics Co., Ltd

