

0...  
2  $\Omega$

0...  
15  $\Omega$

0...  
10 k $\Omega$

## HDT ContiLight 3500



### Features:

- Continuity Tester with Torch Light function
- Optical and acoustical Continuity Tester
- Torch Light function with continuous light
- High current continuity test up to 200 mA
- External Voltage Protection
- For testing cable connections, cable networks, glow lamps, fuses etc.

### Technical Data:

Continuity Test	0...2 $\Omega$ LED, Acoustic, Torch Light 0...15 $\Omega$ LED, Acoustic 0...10 k $\Omega$ LED
Test Voltage	$\leq$ 9 V
Test Current	$>$ 200 mA (0...10 $\Omega$ ) $\leq$ 10 mA
Voltage protection	up to 250 V AC/DC
External Voltage Indication	50...400 V AC/DC
Built according	IEC / EN 61010-1, IEC / EN 61010-031
Power Supply	9 V, IEC 6LR61
Dimension	approx. 130 x 72 x 30 mm
Weight	approx. 260 g

### Scope of supply:

1 pc HDT ContiLight 3500, 2 pcs Test Probes,  
1 pc Battery 9 V, IEC 6LR61, 1 pc Instruction Manual

### Order information

Description	Order No.
HDT ContiLight	3500

**Hoover Dam Technology GmbH**  
In den Engematten 16 · 79286 Glottertal / Germany  
Tel. +49 (0) 7684 907 - 200 · Fax. +49 (0) 7684 907 - 101  
Email: info@hdt-electronic.com · Internet: www.hdt-electronic.com

linking people  
and technology

Shanghai Beihan Electronics Co., Ltd

