

-50...
250°C

LCD

Only
16 g

ThermStick 6201



Features:

- Dig. Mini-Thermometer with Liquid / Needle Probe
- Integrated Data Hold
- Compact Construction
- Protective Sleeve included

Technical Data:

Display	LCD, 3 ¹ / ₂ digit, 1999 Digit	
Measurement Range	-50 °C...250 °C	
Range	Resolution	Accuracy
-50 °C...-20 °C	1 °C	± 3 °C
-19.9 °C...+49.9 °C	0.1 °C	± 2 °C
+50.0 °C...199.9 °C	0.1 °C	± (3 % rdg. + 1 °C)
+200 °C...250 °C	1 °C	± (3 % rdg. + 1 °C)
Temperature change/		
Response time	> 5 K/s	
Power Supply	1 x 3 V, CR 2032	
Dimension (with protective sleeve)	approx. 40 x 30 x 160 mm	
Weight	approx. 16 g	

Scope of supply:

1 pc HDT ThermStick 6201, 1 pc Battery 3 V, CR 2032,
1 pc Protective Sleeve, 1 pc Instruction Manual

Order information Description

HDT ThermStick

Order No.

6201

Hoover Dam Technology GmbH
In den Engematten 16 · 79286 Glottertal / Germany
Tel. +49 (0) 7684 907 - 200 · Fax. +49 (0) 7684 907 - 101
Email: info@hdt-electronic.com · Internet: www.hdt-electronic.com

linking people
and technology

Shanghai Beihan Electronics Co., Ltd

