

Lamp  
test

Optic  
acoustic

Continuity  
& Voltage  
Test

## HDT LampTester 7100



### Features:

- Handy test instrument for swift fault finding in all gas-filled low pressure and high pressure discharge lamps
- For fluorescent lamps the test is carried out without disassembling the UUT
- Built-in continuity tester for chokes, coils, resistors, capacitors, etc. with optic and acoustic display
- Integrated single-pole voltage tester
- The test procedure consists of the comparison between new item and UUT
- Optic and acoustic display for continuity and voltage
- Additional built-in torch light

### Technical Data:

Voltage	approx. 3 kV
Test Frequency	approx. 280 kHz
Field Strength	approx. 100 $\mu\text{V}/\text{m}$
Continuity Range	0...3 M $\Omega$
Test Current	< 7 $\mu\text{A}$
Voltage Indication	LED and acoustical
Voltage Range	60...250 V AC
Frequency	40...60 Hz
Measurement Cat.	CAT II / 300 V
Pollution Degree	2
Safety	IEC 61010
Dimension	255 x 60 x 40 mm
Weight	approx. 170 g

### Scope of supply:

1 pc Lamp Tester 7100, 1 pc Battery 9 V,  
1 pc Instruction manual

### Order information Description

HDT Lamp Tester

### Order No.

7100

**Hoover Dam Technology GmbH**  
In den Engematten 16 · 79286 Glottertal / Germany  
Tel. +49 (0) 7684 907 - 200 · Fax. +49 (0) 7684 907 - 101  
Email: info@hdt-electronic.com · Internet: www.hdt-electronic.com

linking people  
and technology

Shanghai Beihan Electronics Co., Ltd

