

CAT III
300 V

RCD
30 mA

RCD
<300 ms

HDT SocketTester MK2



Features:

- Socket Tester with RCD tripping function
- Simple and easy to use Socket Test with RCD-tripping
- Quick and easy testing of 30 mA RCDs
- Monitors contact voltages and indicated via LED
- PE errors clearly indicated via LCD
- The fixed power plug enables quick and easy testing

Technical Data:

Nominal Voltage	230 V AC
Frequency Range	50...60 Hz
RCD Test Current	30 mA
RCD Test Time	< 300 ms
Contact Voltage Indication	20...25 V AC/DC
PE-Error Indication	25 V AC against ground
Built according	IEC / EN 61010-1
Measurement Cat.	CAT III / 300 V
Dimension	approx. 130 x 72 x 30 mm
Weight	approx. 260 g

Scope of supply:

1 pc HDT SocketTester MK2, 1 pc Instruction Manual

Order information

Description

HDT SocketTester MK2

Order No.

8410

Hoover Dam Technology GmbH

In den Engematten 16 · 79286 Glottertal / Germany
Tel. +49 (0) 7684 907 - 200 · Fax. +49 (0) 7684 907 - 101
Email: info@hdt-electronic.com · Internet: www.hdt-electronic.com

linking people
and technology

Shanghai Beihan Electronics Co., Ltd

