

CAT III
300 V

LED
5

Rotary
Field

HDT Rotary Field Indicator 8110



Features:

- Rotary Field Indicator with phase indication
- Voltage and frequency range suitable for industrial systems
- Phase and rotary indication via LED
- Incl. Test Leads, Crocodile Clamps and Test Probes

Technical Data:

Voltage Range	150...500 V AC (Phase/Phase)
Frequency Range	50 / 60 Hz
Indication	5 LED
Test Current	< 3.5 mA
Duration Time (DT)	continuous operation
Pollution Degree	2
Measurement Cat.	CAT III / 300 V
Protection Degree	IP 40
Safety	IEC/EN 61010, IEC/EN 61557-7
Power Supply	without batteries
Dimension	approx. 130 x 72 x 30 mm
Weight	approx. 190 g

Scope of supply:

1 pc HDT Rotary Field Indicator, 3 pcs Test Leads, 3 pcs Test Probes
1 pc Crocodile Clamp, 1 pc Instruction Manual

Order information Description

HDT Rotary Field Indicator

Order No.

8110

Hoover Dam Technology GmbH
In den Engematten 16 · 79286 Glottertal / Germany

Shanghai Beihan Electronics Co., Ltd.
Tel: +86(0)21-63340274 63340254
Fax: +86(0)21-63340789 Ext 16
E-mail: info@beha.com.cn

